




# Always check our website for the most updated specifications: www.americh.com









Tub pictured with optional grab bar and waste & overflow.

All bathtub dimensions are  $\pm 1/2$ ".

### **CODES AND COMPLIANCE**

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7
- ANSI A112.19.8 ASTM F462-79

Contact Americh for additional approvals.

### **DIMENSIONS**

72" x 48" x 21" deep (1829 x 1219 x 533 mm) Whirlpool Operating Gallons = 60 (Liters = 227) Gallons to Overflow = 99 (Liters = 375)

# **ELECTRICAL REQUIREMENTS**

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

# Builder Series Luxury Series Platinum Series (pump and blower location only) Airbath System III LEGEND: P PUMP B BLOWER JET ROTARY JET DUAL SUCTION LIGHT ON/OFF CONTROL GRAB BAR ACCESS PANEL (MINIMUM 16" x 20")

						Α	С	CE	S S O R	I E S			
Apron	Grab Bars				Pillow				Neck	Tile	Installation		
	9"	14"	16"	Madison	Rail	13"	17"	Angle	Head Support Systems	Massage Flange		Deck Mount	Undermount
	•	•	•									Yes	No
= option is available												ole	

# INSTALLATION TIPS

- Install product according to our Owners manual and local codes.
- All units with an Airbath III may be 1 1/2 2 1/2" higher than stated.
- All whirlpool or Airbath™ unit requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary.
- For oval or specialty shapes. Americh recommends you wait until you have the actual unit or contact us for a template.