Cat. No. ATFRECN59AIG-XX





L: 59" W: 30" H: 24"

Water depth: 18-½" to top of tub Water depth: 14-¾" to overflow

Overflow slot lenght: 4-7/8"

Center drain to back of rim: 14-3/8" Bottom of drain to floor: 3-5/8" Bathing well to floor: 4-3/8"

The following is recommended for ATFRECN59A tubs:

•Faucet: part #7901 or 7913



For easier instalaltion we recommend use of 5598-ITD Easy Install Rough In Kit

Gallon Capacity with OF: 39
Shipping Weight: 144 lbs.
Empty Weight: 84 lbs.
Filled Weight with OF: 410 lbs.

Features:

- ► Interior and exterior walls acrylic sheets
- ▶ Drain and overflow covers included (available in 6 finishes)
- ► Overflow slot with integrated drain
- ► Drain included
- ► Rim ends are 2-3/4" wide side are 1"
- ► No faucet holes
- ► Includes built-in adjusters
- ► Angle slope of tub: 31°
- ► Tub is thoroughly inspected before shipment
- ▶ Option to add foam insulation between tub walls available
- ► Not compatible with air jet system

Finishes:

BN Brushed Nickel
CP Polished Chrome
ORB Oil Rubbed Bronze
PB Polished Brass
PN Polished Nickel

WT White

Custom Colors Available (inside of tub is always white enamel): Painted bathtubs are considered "special order" and are not returnable \$160 Bisque or Black \$250 Designer Color





