

INSTALLATION INSTRUCTIONS

Parts Included

• Faucet body with spout • 2 Handles • 2 Flanges • 2 Wall Connectors with rubber washers

Tools Needed

• Adjustable Wrench • Slip Joint Pliers • Pipe Putty or Teflon Pipe Tape •



- 1. Shut off hot and cold water supply under sink. Plug sink drain with cloth to avoid losing small parts.
- 2. Thread Flanges over nipples for water supply using teflon tape.
- 3. Thread Wall Connectors on to Flanges using teflon tape.
- 4. Connect Faucet Body to Wall Connectors using teflon tape.
- **5.** Attach handles to faucet body.
- 6. For models with soap dish, thread post into back of faucet body and attached soap dish.
- 7. Turn on your new faucet for the first time. Allow both hot and cold water to run for one minute.

NOTE:

- **1.** Use teflon tape on all threaded connections.
- 2. Flush line before faucet installation to remove debris
- **3.** Take care not to keep plumber's putty on any finish to corrode finish of faucet surface.
- **4.** Take care not to damage the finish with tools during installation.

Care and Maintenance:

- 1. To clean, simply wipe with a clean soft cloth.
- **2.** Please do not use sponge. Also, do not use abrasive cleansers or solvents to clean the faucet.