# BROCTON 68" CAST IRON ROLL TOP TUB

Cat. No. CTRN67





L: 68" W: 30-1/8"

H: 24-3/4" (from floor to top of tub)

19-1/4" (from bottom of tub to top of tub)

The following is recommended for CTRN67 tubs without faucet holes:

•Faucets: part #4602, 4604 or 7082

•Rigid, freestanding supplies: part #4502

•Leg tub drain: part #5599

Gallon Capacity: 57
Shipping Weight: 502 lbs.
Empty Weight: 309 lbs.
Filled Weight: 785 lbs.

#### Features:

- ► Inside finish is white enamel
- ► Cast Iron Ball and claw feet available in 8 finishes or unfinished
- ► Tub exterior is white (epoxy)
- ► No faucet holes
- ► Pre-drilled overflow hole
- ► Non-skid strips
- ► Feet are attached and leveled before shipment
- ► Tub is thoroughly inspected before shipment

#### **Foot Finishes:**

**UF** Unfinished

**BL** Painted Black

**BQ** Painted Bisque

**PB** Polished Brass



**CP** Polished Chrome


WH Painted White


PN Polished Nickel

**SN** Brushed Nickel

**ORB** Oil Rubbed Bronze

**Custom Colors Available** (inside of tub is always white enamel): Painted bathtubs are considered "special order" and are not returnable \$160 Bisque or Black \$250 Designer Color





# TUB WALL MOUNT FILLER WITH HANDSHOWER


Cat. No. 4602







Adjustable Swivel Mounts



#### Features:


- ▶ Brass construction
- ► Elephant spout length is 5-3/4"
- ► Flow rate is 3.7 GPM
- ► Available with porcelein lever (4602-PL) or metal cross handles (4602-MC)
- ► Telephone handshower with cradle and hose
- ► Handshower flow rate 2.5 GPM
- ► Handshower includes backflow preventer
- ► Swivel mounts adjust centers from 3" to 12"
- ► Faucet centers are 7" without swivel mounts
- ► For tub wall mount installation
- ► ¼ turn ceramic disc cartridges
- ►IAPMO approved
- ► To be used with double offset bath supplies, Part #5576
- ► This faucet can also be used with rigid freestanding supplies, Part #4502 with adjustable swivel mounts removed

#### Finishes:

BP Polished Brass
CP Polished Chrome
ORB Oil Rubbed Bronze

**SN** Brushed Nickel **PN** Polished Nickel





Dimensions are nominal and may vary. Dimensions and specifications subject to change without notice.

09/21/2018

# FREESTANDING BATH SUPPLIES

Cat. No. 4502-PL



▶ 0.800" Outer diameter

▶ 0.595" Inner diameter

▶ 0.090" Thickness of wall



H: 30" (30-1/2" with nut)



#### **Features:**

- ▶ 5" Shaft included
- ► Stops included
- ► ½" Pipe thread inlet
- ▶¾" Flare outlet
- ► Wall support assemblies included
- ► Porcelain lever handles
- ► IAPMO approved
- ► Available in 5 finishes
- ► Should not be used with leg tubs that have factory drilled holes.


#### Finishes:

**CP** Polished Chrome

PN Polished NickelBP Polished Brass

ORB Oil Rubbed Bronze

SN Brushed Nickel



Use on concrete floors requires special installation. We recommend using a plumbing proffessional.

Dimensions are nominal and may vary. Dimensions and specifications subject to change without notice.

## LEG TUB DRAIN

Cat. No. 5599






Escutcheon Height: 1-1/4"

#### **Features:**

- ► Twist-and-lift stopper
- ► Includes deep escutcheon
- ► Height adjustable 15"-18"
- ▶ Depth adjustable 12"-14"
- ► Includes deep escutcheon
- ►IAPMO approved
- ► Available in 5 Finishes

#### Finishes:

CP Polished ChromeBP Polished BrassSN Brushed NickelPN Polished NickelORB Oil Rubbed Bronze



Dimensions and specifications subject to change without notice.

# "D" SHAPED SHOWER ROD

Cat. No. 4145





#### Features:

- ▶ 1" Solid brass tubing
- ► Includes rectangular flanges(#300)
- ► Includes two "D" rod loop connectors (#331)
- ► Available In 3 Sizes: 48", 54", and 60" (#4145-48, #4145-54, and #4145-60)
- ► All rods come as four pieces
- ► Ceiling Supports Available (#340)
- ► Available in 5 finishes



"D" Rod Loop Connector

#### Finishes:

**CP** Polished Chrome

SN Brushed Nickel


**BP** Polished Brass

**ORB** Oil Rubbed Bronze

PN Polished Nickel



Rectangular Flange



Measurements Show Different Lengths For Each Size Rod.

Dimensions are nominal and may vary. Dimensions and specifications are subject to change without notice.