

NewHome Bath and Mirror

Original ClearMirror



CLEARMIRROR

Original ClearMirror Specifications

Operation

ClearMirror® is an ultra thin heater that adheres to the back of a mirror and is wired to the same power supply as the bathroom light fixture, fan or separate switch. When turned on, the pad heats up, preventing condensation on the surface of the mirror.

The size of the ClearMirror determines the area of the mirror that will remain dry and fog free. Depending upon humidity and time, the heat will radiate and may clear a larger area.

Standard Sizes and Wattage

12"x12" uses 26 Watts

14"x14" uses 35 Watts

20"x20" uses 65 Watts

20"x30" uses 102 Watts

Power Supply

All standard sizes use 110/120 volts.

Maximum Operating Temperature

102° Fahrenheit

Approvals

UL and C-UL listed.

Meets CSA international standards.

Approved by New York City's Bureau of Electrical Control.

Connection

Standard 2-42-inch silicone wire leads that exit the ClearMirror from the top center edge.

Adhesion to Mirror

Pre-applied acrylic PSA with removable contact paper.

Pad Thickness

1/32 – inch

Warranty

5-year replacement warranty against product defects.

Warning

Not for use in showers or steam showers. Use the Shower ClearMirror for those applications.

Caution

Do not install on exterior walls in extremely cold climates unless the wall is well insulated.

Caution

Do not attempt to remove the heating pad once it is adhered to the mirror.

Note

Mirror is not included.

Product is intended to work behind your existing mirror.