
Job Type:





PRODUCT DESCRIPTION

Reeded glass tubes are paired with ribbed aluminum LED housings in your choice of Gold or Matte Black finishes. The interior frosted glass diffusers soften the high-powered LED boards concealed within. The low-voltage light sources are driven by a commercially rated range voltage LED drivers with universal dimming, allowing them to be used in both residential and decorative commercial or hospitality applications. ADA compliant sconces are a welcome companion to the series as well as the fully metal stem hung pendant option designed without glass and uses a JA8 Listed LED GU10 lamp instead of dedicated LED.



MEASUREMENTS DIMENSION MAX OAH

CANOPY

LUMENS

DIMMABLE

COLOR_TEMP

BULB

CRI

Contemporary

Lighting™

:	22.5" L x 22.5" W x 17" H
•	140" OAH
	22.5" W x 1.5" H x 22.5" L
	37.5 lb
•	0, 10 10

HANGING WEIGHT LAMPING

INPUT VOLTAGE :120-277V : 5,400 Rated (3,840 Del.) : 12 x 5W LED PCB Integrated , 60W Total BULB INCLUDED : (Integrated) : Only at 120V : 90 CRI : 3000K

FINISHES OPTION



GLASS Clear Ribbed 144

MATERIAL Aluminum

RATINGS cETLus Dry Location



ADDITIONAL

SLOPE: 30 RATED LIFE 25000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com