





PRODUCT DESCRIPTION

A central, cylinder diffuser of opal white acrylic diffuses LED lighting within a cavity of thin ribbed glass of various lengths. Both imaginative and functional, the bright pendants encase an additional down light recessed within a Naturally Aged Brass or Matte Black housing casting light downward.

MEASUREMENTS

DIMENSION : 4.75" W x 14.5" H x 2.5" Ext

: 4.75" W x 4.75" H MAX OAH

HANGING WEIGHT : 2.43 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 800 Rated (600 Del.)

: 1 x 10W LED PCB Integrated, 10W Total **BULB**

BULB INCLUDED : (Integrated) : Universal 3-in-1 DIMMABLE

: 90 CRI CRI COLOR_TEMP :3000K

FINISHES OPTION



Natural Aged Brass (NAB)

GLASS

Clear Ribbed 144

MATERIAL

Steel, Aluminum, Glass

RATINGS

CETLUS

Damp Location

ADA







ADDITIONAL

RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com