



PRODUCT DESCRIPTION

Elongated tubes of LED light are housed in incredibly small 1" diameter aluminum and suspended by nearly invisible support cables. Engineered to connect the various lengths end-to-end or with use of the rigid, angled adapters, adds endless applications for creativity and function. Each length includes a power feed within a surface mounted canopy and non-electrical support cables that standoff using ceiling anchors. With no additional power source components required, the continuous run pendants in this series are a welcome convenience for commercial applications. Lengths range from 36" to impressive 96" long. Individually, the fixtures provide ample lighting downward with minimal disruption to the architectural sight lines of a space. Available in Black, White, and brushed Aluminum finishes these are exemplary streamlined forms with functional purpose.

121" *Max OAH

*max overall height

MEASUREMENTS

DIMENSION : 47" L x 1.5" W x 1.25" H

MAX OAH : 121" OAH

: 5" W x 1" H x 5" L CANOPY

HANGING WEIGHT : 3.53 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 2,650 Rated (2,100 Del.)

BULB : 1 x 34W LED PCB Integrated, 34W Total

BULB INCLUDED : (Integrated) DIMMABLE : Universal 3-in-1

CRI : 90 CRI

COLOR_TEMP : Select 30/35/40K

FINISHES OPTION



White (WT)

GLASS

Frosted 90

MATERIAL

Acrylic, Aluminum

RATINGS

cETLus Dry Location



ADDITIONAL

RATED LIFE 50000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com