





PRODUCT DESCRIPTION

Elongated tubes of LED light are housed in incredibly small 1" diameter aluminum and suspended by nearly invisible support cables. Engineered to connect the various lengths end-to-end or with use of the rigid, angled adapters, adds endless applications for creativity and function. Each length includes a power feed within a surface mounted canopy and non-electrical support cables that standoff using ceiling anchors. With no additional power source components required, the continuous run pendants in this series are a welcome convenience for commercial applications. Lengths range from 36" to impressive 96" long. Individually, the fixtures provide ample lighting downward with minimal disruption to the architectural sight lines of a space. Available in Black, White, and brushed Aluminum finishes these are exemplary streamlined forms with functional purpose.

MEASUREMENTS

DIMENSION : 93.7" L x 1.5" W x 1.25" H

MAX OAH : 121" OAH

CANOPY : 4.5" W x 1.25" H x 16" L

HANGING WEIGHT : 6.5 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 5,250 Rated (4,200 Del.)

BULB : 1 x 68W LED PCB Integrated, 68W Total

BULB INCLUDED : (Integrated) DIMMABLE : 30-35-40 CRI : 90 CRI

COLOR_TEMP : Select 30/35/40K

FINISHES OPTION



Satin Aluminum (SA)

White (WT)

GLASS

Frosted 90

MATERIAL

Acrylic, Aluminum

RATINGS

cETLus Dry Location





ADDITIONAL

RATED LIFE 50000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



121"

93.7

*max overall height

WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269