A19LED103-6PK

CRI 80 3000K 600 Lumens Filament LED bulb



Performance

- LED bulb is designed to provide 15000 hours of life
- Energy-saving & Super bright, saving 75% energy compared
- ETL and FCC compliant, for use indoor only.

Construction

• IP20 Waterproof

Installation

- To ensure safety, please disconnect power before installation and changing Bulb.
- Size:Φ2.36" *H4"







Specifications


pecifications			
Category	Light Bulb	Individual Box Weight Per Unit (Lbs)	0.13
Shape	A19	Inner Package Length (Inch)	8.12
Bulb Base Type	E26	Inner Package Width (Inch)	5.44
Bulb Base Finish	Gold	Inner Package Height (Inch)	5.52
Color Temperature	3000K	Inner Package Weight Per Unit (Lbs)	1
Beam Angle	360°	Inner Package Quantity	6
Finish	Clear		
CRI	80		
Average Life (Hours)	15000		
Estimated Yearly Energy Cost (11 ⊄/Kwh)	0.72		
Life Based On 3Hrs/Day (Years)	13.7		
Product Length (Inch)	N/A	Lamp Type	LED filament
Product Width (Inch)	2.36	Bulb Shape	A Lamp
Product Height (Inch)	4	Dry/Wet/Damp	Dry
Product Extension (Inch)	N/A	Energy Star	NO
Product Weight Per Unit (Lbs)	0.07	Power Factor	0.8
Dimmable	Yes	Current	55mA
Watts	6	Lumen/Watt	100
Watt Equivalent	60	Warranty (Year)	2
Lumens	600	DLC (Yes/No)	No
Certification (UL/ETL/FCC)	ETL	Input Voltage	120V;60Hz
Individual Box Length (Inch)	2.56	Housing Material	Glass
Individual Box Width (Inch)	2.56	Lens	Clear Glass
Individual Box Height (Inch)	5.12	Led Type	San'an


A19LED103-6PK

CRI 80 3000K 600 Lumens LED Filament Bulb

Lum Limit Curve

	Dazzle	Quality	Illuminance (ix)							
I	1.15	Α	2000	1000	500	<=300				
	1.50	В		2000	1000	500	<=300			
	1.85	С			2000	1000	500	<-300		
	2.20	D				2000	1000	500	<=300	
	2.55	E					2000	1000	500	<=300






L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	35	39	42	45	48	51	52	54	54
C90	49	51	53	55	58	59	61	62	63
C180	70	75	80	85	89	91	94	95	96
C270	41	42	43	43	43	42	41	41	39

Dimmer Types

Brand	Model#
LEVITON	6672-1LW
LEVITON	6674-P0W
LUTRON	S-600P-WH
LUTRON	MACL-153M-WH
LUTRON	DVCL-153P-WH
LUTRON	D-600PH-3CK
LUTRON	D-600PH-DK
LUTRON	D-600R

Elitco Lighting by Elegant

Luminous Intensity Distribution Curve



The Average Illuminance Effective Figure

