
# A19LED803

## CRI 80 2700K 800 Lumens LED A19



architectural form and versatility to make it an excellent choice for new construction or retrofit applications.

## Performance

- LED A19 is designed to provide 15,000 hours of life
- Energy-saving & Super bright, saving 80% energy compared
- •UL, for use in Dry

## Construction


• Aluminum for excellent heat dissipation

## Installation

• Size:  $\Phi 2.36''(60mm)$ \*H4.21''(107mm)



# 



### Specifications

specifications			
Category	A19	Inner Package Length (Inch)	7.28
Bulb Base Type	LED	Inner Package Width (Inch)	4.92
Bulb Base Finish	NO	Inner Package Height (Inch)	4.92
Color Temperature	2700K	Inner Package Weight Per Unit (Lbs)	0.76
Beam Angle	160°	Carton Package Length (Inch)	15.35
Finish	White	Carton Package Width (Inch)	10.63
CRI	80	Carton Package Height (Inch)	5.71
Average Life (Hours)	15000	Carton Package Weight Per Unit (Lbs)	4.15
Estimated Yearly Energy Cost (11⊄/Kwh)	1.20	Carton Quantity	24
Life Based On 3Hrs/Day (Years)	13.60	Lamp Type	LED A19
Product Length (Inch)	2.36	Bulb Shape	A19
Product Width (Inch)	N/A	Dry/Wet/Damp	Dry
Product Height (Inch)	4.21	Energy Star	N/A
Product Extension (Inch)	N/A	Power Factor	0.7
Product Weight Per Unit (Lbs)	0.072	Current	115mA
Dimmable	NO	Lumen/Watt	81
Watts	10W	Warranty (Year)	3
Watt Equivalent	60W	DLC (Yes/No)	NO
Lumens	800	Input Voltage	120V/60HZ
Certification (UL/ETL/FCC)	UL	Housing Material	Aluminum
Color box Package LENGTH (INCH)	2.38	Lens	PC
Color box Package Width (INCH)	2.38	Led Type	Bridgelux 2835
Color box Package HEIGHT (INCH)	4.84		
Color box Package Weight per Unit (LBS)	0.105		



