

Collection: Halycon Installation manual for:

LD2354 W5"E8. 6"H10. 6"L1

Installation instructions:

- 1. Secure Mounting bracket(P1) to the junction box.
- 2.Insert screws(P2) in side of top unit the mounting bracket.
- 3.Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 4. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 5. "E" wire from the fixture is attaced to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 6.Fix the Back plate(P3) to the Mounting bracket(P1) and tighten by the Nuts(P4). 7.Install the bulbs(bulbs not included) into the lampholder(P8).

The end!

Junction box "L" "N" P5 P6 MAX 290° P7 P8 P9 P9 P9

PARTS LIST

part	picture	Description	Qty	Check list
P1	Ō	Ø4.5″ Mounting bracket	1	
P2	(management)	5/32-32 Screw	2	
Р3		Ø4.7" Metal Back plate	1	
P4		M5 Nuts	2	
P5		L3.9" Metal Rod	1	
P6	 	Cardan joint	1	
P7		Ø2″ Metal Cover	1	
P8	Ī	E26 Lampholder	1	
P9		ø5"Lampshade	1	

L'' = Hot wire

"N" = Neutral wire

"E" = Ground wire