


Collection:Mimi Installation manual for:


LD2451 W5. 9"H5. 9"E8. 3"L1

Installation instructions:

- 1. Secure Mounting bracket(P1) to the junction box.
- 2.Insert screws(P2) in side of top unit the mounting bracket.
- 3.Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 4. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 5. "E" wire from the fixture is attaced to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 6.Fix the Back plate(P3) to the Mounting bracket(P1) and tighten by the Nuts(P4).
- 7.Install the bulbs(bulbs not included) into the lampholder(P9).
- 8.Clip the Glass shade(P10) into the gap of the Gap Dish(P8).
- 9.Rotate the Glass shade(P10) and install the Gap Dish(P8) into the Glass shade.
- 10.Fix the Metal Dish(P7) and tighten the Nut(P6).

The end!





"L" = Hot wire

"N" = Neutral wire

"E" = Ground wire

PARTS LIST

part	picture	Description	Qty	Check	list
P1	Q.	Ø4.5″ Mounting bracket	1		
P2	(hannonna)	5/32-32 Screw	2		
Р3		Ø4.7″ Metal Back plate	1		
P4		M5 Nuts	2		
P5	11(11111)	L2.2" Metal Rod	1		
P6		M10 Nut	1		
P7	200	D3.2" Metal Dish	1		
P8		D3.2" Gap Dish	1		
P9		E26 Metal Cup	1		
P10		D5.9" Glass shade	1		