


MSL1002V1

CRI 80 5000K 1400Lumens LED Security Light



The high performance LED Security Light architectural form and versatility to make it an excellent choice for new construction or retrofit applications.

Performance

- LED Canopy is designed to provide 50,000 hours of life
- UL compliant, for use in Wet locations




Construction



- Die -cast aluminum housing with durable paint finish
- Plastic optical lens is protected by gasket lined tempered PC cover

Installation

- LED Security Light wall mount
- Size: $\Phi 10.5'' \times H 6.10'' \times 9.60''$



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Specifications

Category	Security Light	Inner Package Length (Inch)	11.46
Bulb Base Type	LED	Inner Package Width (Inch)	7.68
Bulb Base Finish	NO	Inner Package Height (Inch)	7.28
Color Temperature	5000K	Inner Package Weight Per Unit (Lbs)	3.18
Beam Angle	270°	Carton Package Length (Inch)	
Finish	Brown	Carton Package Width (Inch)	
CRI	80	Carton Package Height (Inch)	
Average Life (Hours)	50000	Carton Package Weight Per Unit (Lbs)	
Estimated Yearly Energy Cost (11 ¢ /Kwh)	2.89	Carton Quantity	
Life Based On 3Hrs/Day (Years)	45.66	Lamp Type	Security
Product Length (Inch)	10.5	Bulb Shape	Round
Product Width (Inch)	6.1	Dry/Wet/Damp	Wet
Product Height (Inch)	9.6	Energy Star	yes
Product Extension (Inch)	N/A	Power Factor	0.9
Product Weight Per Unit (Lbs)	2.43	Current	200MA
Dimmable	YES	Lumen/Watt	70
Watts	20W	Warranty (Year)	5
Watt Equivalent	N/A	DLC (Yes/No)	N/A
Lumens	1400	Input Voltage	120V-277V
Certification (UL/ETL/FCC)	UL	Housing Material	Aluminum
		Lens	PC
		Led Type	LG 3030