


UL SPECIFICATION

* FIXTURE SHALL BE LISTED FOR LOCATION ONLY AND LABELED AS SUCH. * FIXTURE MUST BE MANUFACTURED IN ACCORDANCE WITH UL STANDARD 1598.

PARTS SPECIFICATIONS ITEM QTY DESCRIPTION

- A (1) SOCKET- UL LISTED/CSA CERTIFIED
 BASE=MEDIUM
 SOCKET=PORCELIN
 SEE LEAD WIRE FOR SOCKET WIRE SPEC.
- B (1) LEAD WIRE- 7" [180] FROM CANOPY UL LISTED/CSA CERTIFIED, AWG #18 105%%DC BLACK AND WHITE WIRE. STRIP 1/2 [12.7], SPLIT 3 [76.2]. FROM TOP OF SCROLL. (SEE CHART FOR COLOR).
- C (1) GROUND WIRE- 7" [180] FROM CANOPY
 1/4 LAY COPPER GROUND WIRE.
 FROM TOP OF SCROLL.
 (SEE CHART FOR TINT).



623-3W-PC-G52	STEEL	POLISHED CHROME FOR 623-3W-PC-G52							
623-3W-GB-G52	STEEL	BRUSHED BRASS FOR 623-3W-PC-G52							
623-3W-BK-G52	STEEL	MATTE BLACK FOR 623-3W-BK-G52	BLACK AND WHITE	COPPER 842639007827	10842639007824				FLORENTINE SCAVO
623-3W-SN-G52	STEEL	BRUSHED SATIN NICKLE FOR 623-3W-SN-G52	BLACK AND WHITE	COPPER 842639007780	10842639007787				ETCHED WHITE
FIXTURE NO.	MATERIAL	FINISH	LEAD WIRE	GROUND WIRE UPC CODE	12OF5	WATTAGE LABEL	INSTRUCTION SHEET	CUL LABEL	GLASS DESCRIPTION

IVO.	TAKTINO.	DESCRIPTION	IVL
ISC	ONFIDENTIAL MATERIAL AND EXCL	MINATION HEREON DEVELOPED BY THIS COMP USINE PROPERTY OF THE L.D. ALIYA CO. DISC RITTEN CONSENT OF THE L.D. ALIYA CO.	

INNOVATIONS

	Sitosita Wille	120.0				01110011011	0.122.	0022					CREATIV	VITY MEETS EVOLUTIONARY DES	SIGN⊕ F
	_1												,		
- 1	D						DRAWN IN	"mm" DIMENSION INDICATED IN [] DIMENSION IN [1 IS FOR REF. ONLY			TITLE				
ſ	С						THIRD ANGLE	TOLERANCES (EXCEPT AS NOTED)				1LT VANITY			
ſ	B CHANGE THE SIZE OF GLASS ACCORDING TO GLASS SAMPLE.	ОТ	TC/21/08	Mark			PROJECTION	DECIMAL NONE ±.031	ANGULAR ± 1/2%%D	FRACTIONA + 1/32	L SC	ALE -	PART NO.		REV.
Ī	A CHANGE THE CONNECTOR SHAPE AND LOWER THE POSITION OF	F SOCKET OT	C/07/08	Mark			(.X ±.015		DRAWN BY CH		ROVEDBY		ARC BAR	
8	REV DEVISION RECORD		DATE	REVISED AF	PPROVED	ECO#	1 + -	.XX ±.010	25/06/010		v	v	ITEM NO.	623-1F	REV _D

