



## JASON S

8328 MacArthur Dr. • North Little Rock, AR 72118

501.771.4477 • Fax: 501.771.2333 Customer Service: 800.255.5766 www.jasoninternational.com

## forma® Collection Specifications RE525 Whirlpool & Soaking





Patents received or pending.

Includes Linear Overflow Drain Assembly

Note: Dimensional Tolerances: +1/4"

Drop-in-Hole Size:28" x 58"Operating Capacity:38 Gal.Overflow Capacity:66 Gal.

Floor Loading / sq.ft.

 (WP/Soaking):
 56.8 / 53.1 lbs.

 Carton Wt. (WP/Soaking):
 101 / 64 lbs.

 Cube:
 26.4 ft.<sup>3</sup>

**Note:** The pump extends approximately 1" past the end radius of the bath. This requires angling the bath into the drop-in hole.

**Construction:** Fiberglass reinforced acrylic bath with Level Form<sup>™</sup> full-support base.

We provide products listed with Intertek ETL SEMKO (Edison Testing Laboratories) U.S. and Canadian and with International Association of Plumbing and Mechanical Officials (IAPMO). Consult factory with your listing requirements.



A 120V system that includes a quiet 1-1/2 HP, 1-speed whirlpool pump, an electronic control, and a 20-minute timer. The keypad also operates the optional Jetted Neck Pillow.



A 120V system that includes a quiet 1-1/2 HP, 1-speed whirlpool pump, bath heater, (2) Chromatherapy mood lights, Automatic Ozone System, an electronic control, and a 20-minute timer. The keypad also operates the optional Jetted Neck Pillow.



A 120V system that includes a quiet 1-1/2 HP, 1-speed whirlpool pump, bath heater, (2) Chromatherapy mood lights, Automatic Ozone System, a digital control with LCD display, low water level and temperature sensors, a 20-minute timer, and Bluetooth Sound Immersion System. Control keypad operates the pump, LED Chromatherapy mood lights, optional Jetted Neck Pillow and shows equipment status, water temperature, and time remaining.