

## Features

- 6 hydromassage jets can be individually adjusted for water flow and direction.
- Variable-speed pump for adjusting hydromassage intensity.
- Adjustable neckjet pillow with 2 jets provides a stimulating, stress-relieving neck massage.
- 10 backjets target the lower back and shoulders to relieve tension and encourage deep breathing.
- Chromatherapy lighting allows you to select a preferred color scheme to suit your mood.
- Built-in heater.
- Remote control.
- Lighted keypad control.
- Generous length provides a spacious bathing area.
- Drilled for grab bars (required); sold separately.

## Material

- Acrylic.

## Hydrotherapy

- 8 effervescence ports deliver gentle, caressing bubbles.
- Whirlpool.
- Neckjets.
- Backjets.
- Chromatherapy.

## Installation

- Drop-in.

## Required Products/Accessories

K-9653 Grab Bars

## Recommended Products/Accessories

K-1601 Bath/whirlpool footstop, removable  
K-7161-AF 1-1/2" adjustable pop-up drain above- or through-floor  
K-24916 Wireless Music Kit  
K-9696 Whirlpool 6-Jet Trim Kit  
K-23726 Drain treatment  
K-23732 Tub & shower cleaner



## Codes/Standards





ASME A112.19.7/CSA B45.10  
CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662  
UL 1795  
CSA C22.2 No. 218.2


## KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty KOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

## Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	Biscuit
	NY	Dune
	G9	Sandbar



### Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Pump: 240 V, 20 A, 50/60 Hz

### Technical Information

All product dimensions are nominal.

Installation: Drop-in  
Drain location: Center  
Basin area, bottom: 41-3/4" x 27-3/16" (1060 mm x 691 mm)  
Basin area, top: 60" x 30" (1524 mm x 762 mm)  
Weight: 140 lbs (63.5 kg)  
Minimum floor load: 44 lbs/ft<sup>2</sup> (214.8 kg/m<sup>2</sup>)  
Water depth: 16" (406 mm)  
Water capacity: 86 gal (325.5 L)  
Cutout: Drop-in, 70-1/2" x 40-1/2" (1791 mm x 1029 mm)  
Electrical component rating: Pump: 240 V, 11 A, 50/60 Hz, 1500 W  
Pump speed: Variable

### Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

This whirlpool is designed for drop-in installation only. It is not suited for use in a three wall alcove with an overhead shower.

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.