

KOHLER

Features

- Comfort Depth® design offers a convenient 19" step-over height while retaining the same depth as a standard 21" bath.
- Integral lumbar support.
- Slotted overflow allows for deep soaking.
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation.
- Textured bottom surface.
- Coordinates with other products in the Archer collection.

Material

Acrylic.

Installation

- Left drain.
- Alcove.

Required Products/Accessories

K-7271 Brass Slotted Overflow Bath Drain

10

K-7272 PVC Slotted Overflow Bath Drain

Recommended Products/Accessories

K-24916 Wireless Music Kit K-23726 Drain treatment K-23732 Tub & shower cleaner



ADA

Codes/Standards

CSA B45.5/IAPMO Z124 ADA ICC/ANSI A117.1

KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty


See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	NY	Dune
	95	Ice™ Grey
166	G9	Sandbar
	K4	Cashmere
	58	Thunder™ Grey
	7	Black Black™






KOHLER


K-1946-L


15" (381 mm) 1-1/4" (32 mm) 11-1/4" (286 mm)



with drain illustrated. (K-7272)

No change in measurements if connected





Technical Information

All product dimensions are nominal.

Installation: Three-wall alcove

Drain location:

45-1/8" x 19-11/16" (1146 mm x Basin area, bottom:

Basin area, top: 52-1/8" x 22-1/16" (1324 mm x 560 mm)

Weight: 58 lbs (26.3 kg)

Minimum floor load: 45 lbs/ft² (219.7 kg/m²)

Water depth: 15-1/8" (384 mm) Water capacity: 57 gal (215.8 L) Minimum flat for 2" (51 mm)

door:

Notes

Measure your actual product for rough-in

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

ADA compliant when installed to the specific

requirements of these regulations.

