KOHLER, Faucets

Aquifer® shower filter K-30646

Features

- Designed to work with handshowers to reduce chlorine and odor in water.
- Reduces chlorine and odor, controls scale, and inhibits the growth of bacteria and algae.
- Reduces skin dryness and irritation and is gentle on your hair
- Filter system attaches to most exposed shower valves, handshower hoses and wall elbows with a simple threaded connection.
- 4.0 gpm (15.1 l/min) maximum flow rate at 20 psi (1.3 bar).
- Filter media lasts up to 8,000 gallons (30,000 liters) or 6 months.
- Recommended filter cartridge replacement every 6 months.
- Intuitive filter replacement indicator.
- Optional subscription service automatically sends you a new filter every 3, 6, 9, or 12 months.
- Includes one filter cartridge.
- Simple, elegant design to complement a variety of bathroom styles.

Material

Solid metal and acrylic construction.

Recommended Products/Accessories

K-30647 shower filter replacement

K-8520 hotel handshower kit

K-9059 Contemporary Handshower Kit

K-76330 Shower arm with 3-way diverter

K-76331 Shower arm with 2-way diverter

K-76332 Wall-mount rainhead arm with 3-way diverter

K-76333 Wall-mount shower arm with 2-way diverter

K-76336 Rainhead arm with 3-way diverter

K-76337 Rainhead arm with 2-way diverter

K-76466 Handshower Kit

K-98361 G90 Slidebar Kit

K-98362 Handshower Kit

K-99242 Deluxe Slidebar Kit with Handshower, 2.0 gpm

K-99243 Deluxe Slidebar Kit

K-99898 G110 Premium Handshower Kit

K-99899 Premium Slidebar Kit

Included Components

Product consists of:

K-30647 shower filter replacement

Additional Components:

One filter cartridge



Codes/Standards

None Applicable

KOHLER® Water Filter Systems Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes


Color tiles intended for reference only.

Color Code Description

CP Polished Chrome



KOHLER, Faucets



Technical Information

All product dimensions are nominal.

Drain included: No

Notes

Install this product according to the installation instructions.

Replace filter cartridge every 6 months.

