

Features

- Two-piece design.
- Round-front bowl offers an ideal solution for smaller bathrooms and powder rooms.
- 1.28 gpf (4.8 lpf).
- Right-hand Polished Chrome trip lever.
- Tank cover locks included.
- Combination consists of the K-4467-TR tank and the K-4197 bowl.
- Coordinates with other products in the Wellworth collection.

Technology

- Single-flush gravity uses the force of gravity and a precisionengineered tank, bowl, and trapway to create a strong siphon during flushing.
- KOHLERs canister flush valve harnesses the natural force of gravity and optimizes flushing performance.
- Class Five® flushing technology offers virtually plug-free performance and rinsing power for a clean bowl.

Installation

- Standard 12" (305 mm) rough-in.
- Three-bolt quick-connect installation.
- Seat and supply line sold separately.

Water Conservation & Rebates

Eligible for consumer rebates in some municipalities.

Recommended Products/Accessories

K-4639 Cachet® Quiet-Close™ Round-Front Toilet Seat K-5589 Purefresh® Round-Front Toilet Seat K-76923 Puretide[™] Quiet-Close[™] Round-front manual bidet Color tiles intended for reference only. toilet seat K-5420 Low-Profile Bolt Caps K-9379 Trip Lever 1023457 Wax Ring/Hardware Kit 1265114 Connector Hose K-23726 Drain treatment

Included Components

Product consists of: K-4197 Round-Front Bowl K-4467-TR Toilet tank with cover locks, 1.28 gpf Additional Components: Bolt cap accessory pack Tank accessory pack Tank cover Trip lever



Two-piece round-front 1.28 gpf toilet

Wellworth®

K-3997-TR



Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense®

KOHLER® Toilets and Seats Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color Code Description


| 0 | White |
|----|---------|
| 96 | Biscuit |





Wellworth®

Two-piece round-front 1.28 gpf toilet K-3997-TR



Technical Information

| All product dimensions are nominal. | | |
|-------------------------------------|------------------------------------|--|
| Toilet type: | Two-piece, Floor-mount | |
| Waste Outlet: | Floor | |
| Bowl shape: | Round-front | |
| Flush type: | Class Five® | |
| Trap passageway: | 2-1/8" (54 mm) | |
| Water Consumption | | |
| Full: | 1.28 gpf (4.8 lpf) | |
| Water surface size: | 10-1/2" x 7-3/4" (267 mm x 197 mm) | |
| Rim to water surface: | 5-1/4" (133 mm) | |
| Rough-in: | 12" (305 mm) | |
| Seat-mounting holes: | 5-1/2" (140 mm) | |
| | | |

Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

