

### Features

- Available with lever handle.

### Material

- Brass.
- KOHLER finishes resist corrosion and tarnishing.

### Installation

- Bath-mount or deck-mount installation options.

### Required Products/Accessories

K-408-K Bath-mount Transfer Valve

or

K-409-K Deck-mount Transfer Valve

### Recommended Products/Accessories

K-23723 Faucet cleaner



ADA CSA B651 OBC

### Codes/Standards

ASME A112.18.1/CSA B125.1

ADA

ICC/ANSI A117.1

CSA B651




OBC


### KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CP	Polished Chrome
	AF	Vibrant® French Gold
	PB	Vibrant® Polished Brass
	BN	Vibrant® Brushed Nickel



**Technical Information**

All product dimensions are nominal.

**Notes**

Install this product according to the installation instructions.

Bath and handshower outlets required for two-way transfer valve.

Bath, handshower, and auxiliary outlets required for three-way transfer valve.

When used as a two-way transfer valve (bath and handshower), the installer must cap the auxiliary outlet. Do not install spouts with flow restrictors or shower units on the bath outlet.

For installation on cast iron baths, collar should be installed with flange facing downward.

Opening in cast iron must be 1-7/8" D. minimum.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.