

# Whitehaven®

Under-Mount Apron-Front Kitchen Sink K-6488

## Features

- 36-inch minimum base cabinet width.
- Single bowl.
- 9-inch depth.
- Shortened apron allows sink to be used in most standard cabinetry or retrofitted to existing standard cabinetry.
- Self-Trimming apron overlaps the cabinet face for easy installation and beautiful results.
- No faucet holes.
- Basin slopes 2 degrees toward drain to minimize water pooling.
- Offset drain increases workspace in the sink and storage space underneath.

### Material

• KOHLER<sup>®</sup> enameled cast iron.

### Installation

Under-mount apron-front.

### **Recommended Products/Accessories**

K-6639 Sink Rack K-8801 Sink Strainer K-8799 Sink Strainer

### **Optional Products/Accessories**

K-11352 Disposal Flange with Stopper K-9000 P-Trap



## Codes/Standards

ASME A112.19.1/CSA B45.2

## KOHLER<sup>®</sup> Enameled Cast Iron Kitchen Sink Lifetime Limited Warranty

See website for detailed warranty information.

## **Available Colors/Finishes**

Color tiles intended for reference only.


Color	Code	Description
	0	White
	FF	Sea Salt™
	96	Biscuit
	47	Almond
	FD	Cane Sugar™
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	FT	Basalt
	58	Thunder™ Grey
	20	Suede
	KA	Black 'n Tan
	FP	Caviar
	7	Black Black™
	GRL	Grey Lavender
	DGB	Indigo Blue



## Whitehaven®



Under-Mount Apron-Front Kitchen Sink K-6488



## **Technical Information**

All product dimensions are nominal.		
Bowl configuration:	Single	
Installation:	Under-mount	
Min. base cabinet width:	36" (914 mm)	
Bowl area (Only):	Length: 30-3/4" (781 mm) Width: 18-1/16" (459 mm) Bowl depth: 9" (229 mm)	
Drain hole:	3-5/8" (92 mm)	
Template:	1156910-7, required, included 1211449-7, required, included	

## Notes

Install this product according to the installation instructions.

NOTICE: Countertop manufacturer or cutter must use the current product template available at www.kohler.com, or by calling 1-800-4KOHLER. Kohler Co. is not responsible for cutout errors when the incorrect cutout template is used. IMPORTANT! The distance from the top edge of the cabinet to the top of the cabinet door must be at least 6-7/8" (175 mm) to install this sink.

