

Britt™ All-in-One Commercial Filter Faucet

KFF-1691

Congratulations on the purchase of your new Kraus plumbing fixture!

Please keep the box and packaging materials until your product is completely installed. If you have any questions, require technical assistance or have any problems with your product:



DO NOT RETURN TO STORE

Please contact our Customer Service Team 1-800-775-0703 / customerservice@kraususa.com

Have the model number available and retain a copy of your receipt with purchase date for reference.

If for any reason this product does not meet your expectations, please be sure to repack this product in the original box and packaging material to avoid damage during transit.



Prior to Installation:

- Make sure you have all necessary parts by checking the diagram and parts list. If any part is missing or damaged, please contact Kraus Customer Service at 800-775-0703 for a replacement.
- Read all instructions and safety warnings and ensure you have all tools, parts, and equipment necessary for a safe installation.
- Turn off the hot and cold water supply at the angle stops and turn on the old faucet to release any built up pressure. Remove existing faucet. Clean sink or countertop to remove any debris, plumber's putty, or silicone.
- Flush angle stops to release any debris prior to installation.
- Pre-drilled hole size requirement: 1 3/8" (min) 1 1/2" (max)
- Max countertop thickness: 2"

Tools you will need:



Adjustable Wrench



Phillips Screwdriver



Supply Lines



Silicone Sealant



Safety Goggles

Care & Maintenance


To keep the product clean & shining, follow the steps below:

- Rinse with clean water & dry with a soft cloth 1.
- 2. Do not clean with soaps, acid, polish, abrasives or harsh cleaners
- 3. Do not use cloth with a coarse surface
- 4. Unscrew the aerator and clean when necessary

This installation manual is subject to change without further notice.



Diagram and Parts List




- A. Spray Head
- B. Faucet Body
- C. Mounting Hardware
- C1. Rubber & Metal Washer
- C2. Mounting Nut
- C3. Mounting Screw
- D. Flange & Washer
- E. 2.5 mm Hex Wrench
- F. Aerator Key
- G. 3-Way Connector
- H. 1/4 to 3/8 Connector x 2
- I. EZ-Weight
- J. Plastic Stabilizing Base

For technical assistance or replacement parts, please contact Kraus^o

Customer Service and one of our representatives will be happy to help:


Toll-Free: 800-775-0703 or customerservice@kraususa.com

Faucet Dimensions



Installer Tip:


Step 1. Install the faucet assembly



Before installation, ensure that the flange (D) is placed on the bottom of the new faucet assembly (B). Insert the faucet body and all hoses through the hole in the sink.

- 1. Install the pull down hose with connector first.
- 2. Install the hot and cold inlet hoses.
- 3. Install the supply hose.


Step 2. Secure the faucet assembly



Install the plastic washer and metal washer (C1) onto the threaded mounting shank. Thread the nut (C2) onto the mounting shank. Lock the nut (C2) into position by tightening the screws (C3). Do not overtighten.

NOTE: If the stainless steel sink is thinner than 5mm you **MUST** use the plastic stabilizing base (J).


Step 3. Connecting the filter connection and water line



Connect the 1/4 in. water line from the filtration system by pushing the line into the connector (G). Pull down on the 1/4 in. line slightly to ensure the quick connect fitting has engaged.

NOTE: The filter activates by pressing the top button on the sprayer.

NOTE: Use the 1/4" to 3/8" connector if you have a 3/8" tube.




Connect the 3/8 in. water line from the filtration system by pushing the line into the connector (G). Pull down on the 3/8 in. line slightly to ensure the quick connect fitting has engaged.

NOTE: The filter activates by pressing the top button on the sprayer.


NOTE: Use the 1/4" to 3/8" connector if you have a 3/8" tube.

Step 4. Attach the counterweight




Step 5. 1/4 Filter Connection (optional-sold separately)

Thread the nut on the supply line onto the outlet of the water supply valve and tighten with a wrench. Do not overtighten. (use 3-Way Connector for Cold valve if needed)




Step 6. 3/8 Filter Connection (optional-sold separately)

Thread the nut on the supply line onto the outlet of the water supply valve and tighten with a wrench. Do not overtighten. (use 3-Way Connector for Cold valve if needed)




Step 7. Connect the waterlines



Thread the nut (1) on the supply line onto the outlet of the water supply valve (2) and tighten with wrench. Do not overtighten.

NOTE: Please make sure filter washers are installed before connecting to the main valve.


Step 8. Flush and check for leaks



Pull hose assembly out of spout and remove spray head by unscrewing from hose in a counterclockwise direction. Hold the end of the hose down into the sink and turn the faucet on to the warm position. Flush water lines for one minute to flush away any debris. Check for leaks.

Re-tighten any connections if needed. Do not overtighten. Reinstall spray head by hand tightening it back onto the spray needed. After installation is completed, turn on the hot and cold water supplies to check for leaks.

Replacement Parts



Replacement	Finish/Color	Part #
Parts List		
1. Sprayer Head	CH,SFS,MB,BG*	KP46035
2. Sprayer Hose	CH,SFS,MB,BG*	KP46036
Assembly		
3. Spring	CH,SFS,MB,BG*	KP46027
4. Sprayer Seat		KP46037
5. Sprayer Support	CH,SFS,MB,BG*	KP46028
Assembly		
6. Handle Assembly	CH,SFS,MB,BG*	KP46029
7. Cartridge Cover	CH,SFS,MB,BG*	KP46041
8. Locking Nut		KP46042
9. Cartridge		KP46012
10. Base Seat Assembly	CH,SFS,MB,BG*	KP46030
11. Rubber Washer		KP46004
12. Metal Washer		KP46006
13. Mounting Nut		KP46007
14. Mounting Screw		KP46008
15. O-Ring		KP46032
16. 3-Way Connector		KP46031
17. 1/4 to 3/8 Connector		KP46033
18. Quick Connector		KP46043
19. 1.8GPM Flow	WH*	KP46011
Restrictor		I/D40040
20. EZ-Weight 21. Hex Key		KP46040 KP46017
22. Aerator Key		KP46034
23. Filter Washer		KP46024
24. Plastic Stabilizing Base		KP46005
25. Mounting Hardware Kit (includes KP46004, KP46006, KP46007, KP46008)		KP46038

^{*}Denotes faucet component color options:

CH - Chrome

SFS - Spot Free Stainless Steel

MB - Matte Black

BG - Brushed Gold

BL - Black

WH - White

Troubleshooting

If you have followed the instructions carefully and your faucet still does not work properly, take the following corrective steps:

PROBLEM	CAUSE	ACTION
Leakage under faucet handle	Locking nut has come loose or cartridge needs to be reseated.	Remove button located at top of handle. Loosen set screw with hex wrench. Remove handle and unscrew cartridge cover by hand. Tighten locking nut with an adjustable wrench.
Water does not shut off completely	Cartridge may need to be adjusted or replaced.	Remove button located at top of handle. Loosen set screw with hex wrench. Remove handle and unscrew cartridge cover by hand. Unscrew locking nut with an adjustable wrench. Remove ceramic disc cartridge. Check for cracks, and if O-ring is seated correctly. Reseat cartridge.
Leaking between spray head and the hose	Spray head may be loose or washer is not seated correctly in the hose connection.	Tighten spray head by hand until snug. Make sure washer is seated correctly.
Hose does not retract	Weight may be installed incorrectly.	Readjust weight on hose.
Low flow	Aerator may be clogged	Unscrew aerator with aerator key. Hold tip of spray head and turn on water to flush debris.
	The screen filter in the hose connectors is dirty.	Turn off the water supply at water valve and unscrew the hose connectors from water supply lines. Clean the screen in the water lines with hot water, removing any debris or calcium build up.

Codes/Standards Applicable:







ASME A112.18.1 1.8GPM 6.8L/min maximum

Faucet

Kraus USA Plumbing, LLC ("Kraus") extends this warranty to the original purchaser for personal household use of the Faucet when purchased from an authorized Kraus dealer and in the location of original installation. This warranty is non-transferable.

Kraus warrants the structure and finish of the Faucet to be free from defects in material and workmanship under normal usage for as long as the original purchaser resides in the residence in which the Faucet was first installed.

Kraus warrants the Faucet's sprayhead assembly (including the engine, aerators, structure, restrictors, back flow preventers, sprayer hoses, braided supply line hoses which encompasses nylon, silicon and stainless steel) of the product to be free from defects in material and workmanship under normal usage for a period of one (1) year from the date of purchase.

Kraus warrants the Faucet's cartridge to be free from defects in material and workmanship under normal usage for a period of five (5) years from the date of purchase.

Any product reported to the authorized dealer or to Kraus as being defective within the warranty period will be repaired or replaced with a product of equal value at the option of Kraus.

Commercial Warranty

Kraus USA Plumbing, LLC ("Kraus") warrants its Products for a period of one (1) year to commercial purchasers of Products used in industrial, commercial and business applications.

Care and Cleaning Instructions

Certain cleaning products may cause damage to a Product's finish and use of the following on the Product will void this warranty:

- · Abrasive cleaners such as powders, bleach, ammonia, alcohol or chorine
- · Abrasive pads, steel wool or wire brushes

What is Not Covered

This warranty does not cover Products that were discontinued when purchased or display Products, whether such Products were purchased at discount outlets, unauthorized dealers, and/or sold on clearance. This warranty does not cover any free gifts included with purchase.

This warranty does not cover damage resulting from neglect, misuse (including use for an unintended application), abuse, carelessness, accident, hard water or mineral deposits, exposure to corrosive materials, improper maintenance, alteration of the Product, or failure to follow care, cleaning or installation instructions enclosed with your Product. Kraus recommends that all Kraus Products be installed by a fully licensed and insured trade professional with experience in the installation of bathroom and/or kitchen manufactured goods.

How to Make a Warranty Claim

If you are a **consumer purchaser**, please contact a Kraus Customer Service Representative at: Kraus USA Plumbing, LLC
12 Harbor Park Drive
Port Washington, NY 11050
Toll-free 800-775-0703
Customerservice@kraususa.com

If you are a **plumbing contractor or trade professional**, please contact a Kraus Pro Representative at: Kraus USA Plumbing, LLC 12 Harbor Park Drive Port Washington, NY 11050 516-801-8955 Proservice@kraususa.com

If you are an **authorized partner**, please contact a Partner Support Representative at: Kraus USA Plumbing, LLC
12 Harbor Park Drive
Port Washington, NY 11050
516-801-8954
Partnersupport@kraususa.com

In requesting warranty service, please be ready to provide your proof of purchase and a description of the problem. Shipping charges will be covered for the first (1) year of the warranted replacement part or product (HI, AK, and Puerto Rico shipping charges may apply). International shipping fees are not included.

Limitation on Duration of Implied Warranties

Please note that some states/provinces (including Quebec) do not allow limitations on how long an implied warranty lasts, so the below limitations may not apply to you. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, ANY IMPLIED WARRANTY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE, IS LIMITED TO THE STATUTORY PERIOD OR THE DURATION OF THIS WARRANTY, WHICHEVER IS SHORTER.

Limitation of Special, Incidental or Consequential Damages

Please note that some states/provinces (including Quebec) do not allow the exclusion or limitation of special, incidental or consequential damages, so the below limitations and exclusions may not apply to you. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THIS WARRANTY DOES NOT COVER, AND KRAUS USA PLUMBING, LLC SHALL NOT BE LIABLE FOR, ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LABOR CHARGES TO REPAIR, REPLACE, INSTALL OR REMOVE THIS PRODUCT), WHETHER ARISING OUT OF BREACH OF ANY EXPRESS OR IMPLIED WARRANTY, BREACH OF CONTRACT, TORT, OR OTHERWISE.

This warranty gives you specific legal rights, and you may also have other rights which vary from state/province to state/province.

Download the Kraus Care & Maintenance Guide at: http://www.kraususa.com/maintenance

IMPORTANT

Register Your Kraus Product

Activate Your Warranty **Access** Premium Customer Support **Get** Product Information

REGISTER TODAY

http://www.kraususa.com/registration











