



inkasink

V030

STAINLESS STEEL MOSAIC FARMHOUSE

DETAILS

Satin Nickel Exterior Stainless Steel Mosaic Interior Installation: Undermount

AVAILABLE FINISHES

SN Satin Nickel

SPECIFY WHEN ORDERING

Drain Model and Finish (Drain is grouted into sink)

AVAILABLE DRAINS

D0033.5" Basket Strainer**D007**Disposal Flange

INSTALLATION

Drain should be installed first.

DROP-IN: Cut opening large enough for the sink to be "dropped in" to countertop.

UNDERMOUNT: Cuts in countertop are up to the discretion of the installer. Clips or other installation method must be provided by the fabricator/installer.

Use 100% silicone to adhere sink to countertop. Clean any excess silicone from sink surface.

CARE

Clean with mild soap. No abrasive chemicals

WARRANTY

Linkasink warranties our product to be free from manufacturing defect for the life of the product. Warranty does not cover abuse.

DIMENSIONS WILL VARY

DO NOT use this sheet as a guide for countertop cuts. Due to the handmade nature of each product, templates are not provided.

Contact: 1.866.395.8377 sales@linkasink.com Linkasink may make changes to specifications without notice. Visit <u>linkasink.com</u> for updated specification sheet. 5/1/2019