## WRAP LED | 4' LED CEILING WRAP

## 57521 / 57522 / 57523

- Surface Mountable LED Wrap
- PMMA Acrylic Diffuser
- Dimmable with CL Triac dimmer
- Damp Location Rated
- L70 Project Life of 50,000 Hours
- Color Temperatures of 3000k/4000k
   Suitable for Closets according to NEC Section 410.8 & 410.16
- CRI 90+
- Energy Star
- Title 24 JA8 Compliant

Job Name : \_\_\_\_\_\_ Job Type : \_\_\_\_\_\_ Quantity : \_\_\_\_\_\_ Comments :








## **PRODUCT DESCRIPTION**

The classic Wrap Around is updated with more efficient and uniformly lit LED technology. Safer than harmful fluorescent lighting and longer lasting as well. Meeting today's Energy Star and Title 24 requirements, this product is fully dimmable and achieves a color rendering over 90 without sacrificing light output.



## **MEASUREMENTS**

LAMPING

 MODEL
 DIMENSION

 57521
 48"L x 4"W x 4.5"H

 57522
 48"L x 4"W x 4.5"H

 57523
 48"L x 7"W x 2.5"H

MODEL	BULB TYPE	
57521	40W PCB LED (Integrated	)
57522	40W PCB LED (Integrated	)
57523	40W PCB LED (Integrated	)

	CRI	LUMENS RATED DEL		DIMMABLE
d)	90+	3800 3230	4000K	Triac CL
d)	90+	3800 3230	3000K	Triac CL
d)	90+	4200 4000	4000K	

FINISH:
---------

White (WT)



**MATERIALS:** Acrylic + Steel

**RATINGS:** 

ETL/cETL Damp Location Energy Star Title 24 JA8 Compliant Closets Rated: 410.8 & 410.16



ADDITIONAL: RATED LIFE: 50,000 Hours





WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

INPUT

120V

120V

120V

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com