



A Moen Incorporated Brand

Model: 40812


CORNERSTONE™


Two Handle Laundry Faucet

DESCRIPTION

- Metal construction with chrome plated finish
- 1/2" IPS connections
- 9" spout reach
- Accepts adaptor for seal trap primer (not included)
- Includes both stream straightener and garden hose adaptor
- Six (6) individual boxes per master carton
- Handles withstand aggressive scrubbing cleaners

OPERATION

- Lever-style handles
- Hot side: Turn counterclockwise to open (clockwise to close)
- Cold side: Turn clockwise to open (counterclockwise to close)
- Will operate with less than 5 lbs. of torque
- No grasping motion required to operate the faucet handles

FLOW

- Meets the minimum spout flow is limited to 1.5 gpm (5.6 L/min) at 60 psi

CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous, and brass material
- Single body construction for easy replacement

STANDARDS

- Third party certified to CSA B125, ASME A112.18.1, ANSI A117.1, ANSI/NSF 61/9, IAPMO, and all applicable requirements referenced therein, the Federal Safe Drinking Water Act, California Proposition 65, Illinois, Massachusetts, and Texas
- All CFG products are compliant to all plumbing codes that require 3rd party certification to the applicable plumbing/fitting standards
- Features red/blue hot/cold temperature indicators

WARRANTY – RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information



CRITICAL DIMENSIONS

- This faucet designed to be installed through 3 holes, 1" minimum diameter, 4" centers
- Maximum deck thickness 1.75" (44.5 mm)

