

Decor Radiator

As delivered from factory

horizontal or vertical water tubes: 2-3/4" x 7/16" x 16 ga. 2 to 11 high and 1 to 3 deep for the horizontal: or 5 to 10 wide and 1 deep for vertical	X
convector plates between water tubes: 1 to 4 deep for horizontal and 1 deep for vertical	X
max. working pressure [psi] for standard models	72
no. of connectors – 2 per side	4
side connection – GW 1/2": also called 1/2" BSP female	X
side covers	X
top grille	X
manual vent plug - 1/2"	X
blind plug - 1/2"	X

Added at no charge by Rettig USA

brackets bundled with the radiator: KOM300 - KOM600 for 3H to 11H: KOM-WA11 for 5V to 10V: BBWB/BBCB (BBHKIT) for 2H:	X
---	---

Required for H34 pedastal model

KOM-FOOT1 (SK15) or KOM-FOOT2 (SK14)* - SK15 height adjustment 9"- 14" SK14 height adjustment 5"- 9"nominal: Use ASK10 cover with both	X
---	---

* Lengths up to 2000mm require 2 KOM-FOOT. Longer lengths require 3

Suggested add-on options from Rettig USA

Manual radiator valve with stop - part #: LKD16AN (angle) - or - LKD16SN (straight)	X
Standard Valve Kit - 1 FF16WAC & 1 FF16LAC	X
Thermostatic valve: 2TRV1/2 (vertical angle, inverted angle or straight) 1 per radiator used in conjunction with 1 LKD or 1 FF valve	X
Standard TRV head - part #: 2TRVHD **choose 1 head for each Thermostatc valve	X
Compact TRV head - part #: VINDO TH	X
"Visually Impaired" TRV head - part #: UNI LH	X
Pipe Cover PC8 or PC40 in white or chrome	X
Escutcheons ESC in white or chrome	X
End caps & splice plates for 2H - 4H	X

For addition information please see the following publications:

"Decor 2016 Installation Guide", "Decor Submittal Data", "Radiator Valve Selection Guide", "Radiator Component Guide"