### PARIS MIRROR


PRODUCT SPECIFICATION
SKU :BLHM48353000D/BLHM48356000D

# BACKLIT HARMONY

48 X 35 in 1219 X 889 mm

### FEATURES AND BENEFITS

- LED TECHNOLOGY
- HANG HORIZONTALLY VERTICALLY
- ENERGY EFFICIENT
- SUPER BRIGHT 14400 LUMENS CRI 90+
- DIMMABLE WITH ANY STANDARD MLV/ TRIAC DIMMER WALL SWITCH
- UL CERTIFIED
- DURABLE ( UP TO 120 000 HOURS )
- 5 YEARS WARRANTY



#### **AVAILABLE OPTIONS**

- 6000k LED
- 3000k LED
- CCT LED 2700-6000k
- RGBW LED

### LIGHTING SPECIFICATION

- DIMENSIONS: 48X35 inWEIGHT: POUNDS (LBS)
- IP RATING: 44
- WATTS: ?
- LUMENS: 14400
- INPUT VOLTAGE: 110V
- CRI: 90+

### SAFETY SPECIFICATION

- ENTIRE ASSEMBLY MEETS UL/cUL STANDARDS
- INTERNATIONAL CERTIFICATIONS
- SAFETY BACKED MIRROR

## PARIS MIRROR


BACKLIT HARMONY

48 X 35 in 1219 X 889 mm

PRODUCT SPECIFICATION
SKU :BLHM48353000D/BLHM48356000D

### **INSTALLATION & AFTER CARE INSTRUCTIONS:**

- 110V HARD WIRED ELECTRICAL CONNECTION
- Z BAR INCLUDED
- MIRROR SHOULD BE CONTROLED BY AN ON/OFF WALL SWITCH
- INSTALLATION WIRING MAY BE DIFFERENT WITH MIRRORS EQUIPPED WITH ADDITIONAL OPTIONS.



**MODELS:** 

Back

Base model	Kelvin temperature	Dimensions	Power requrements
BLHM48353000D	3000K	48"W x 35"H x 1.55"D (1219mm x 889mm x 40mm)	110 VAC , ?W
BLHM48356000D	6000K	36"W x 36"H x 1.55"D (914mm x 914mm x 40mm)	110 VAC , ?W

### PARIS MIRROR

PRODUCT SPECIFICATION
SKU:BLHM48353000D/BLHM48356000D

## BACKLIT HARMONY

48 X 35 in 1219 X 889 mm

### **INSTALLATION & AFTER CARE INSTRUCTIONS:**

### Installation:

All Paris Mirror backlit and LED mirrors have been independently tested for compliance with electrical equipment (safety) regulations.

All illuminated and backlit mirrors are IP44 rated.

Illuminated mirrors have been designed and independently tested for compliance to electrical equipment (safety) regulations, and are UL Certified.

LED's have a life expectancy of 120,000 hours of continuous use. All LED light fittings are replaceable and are available through Paris Mirror customer service.

IMPORTANT: Always switch off the electrical supply at the mains during installation and maintenance. It is recommended that fuse

is withdrawn or circuit breaker switched off before installation begins.

Fitting in Bathrooms is subject to all regulations. It is not suitable for product installations in Saunas, Steam Rooms, or shower cubicles, and it is recommended for permanent installation.

### Care Safety:

Wear suitable eye wear protection when drilling. Use caution when using power tools near water, beware of hidden cables or pipes.

Take care if drilling on tiled surfaces in case the drill slips. A piece of masking tape applied to wall before marking out fixing holes will stop drill from moving.

### Cleaning & Maintenance:


It is recommended that the unit is cleaned with a soft, dry, non-abrasive cloth when turned off.

Never use cleaning agents or abrasive

material on any type of surface finish.

Do not strike glass components with hard or pointed items.

Do not place very hot or cold items against or close proximity to glass surfaces.



### 120V DIMMABLE LED DRIVER INCLUDED

- 1- Decide on wall positional placement.
- 2- Prepare & install wall hooks measured to distance between mirror's anchors.
- 3- Match & attach 3 electrical wires from mirror to home electrical wires: Live to Live, Ground to Ground, Neutral to Neutral.
- 4- Hang and affix to wall.