



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	1-600	WIDESPREAD HOT AND COLD VALVES W/PLASTIC NUTS	1
1.1	1-109	WIDESPREAD VALVE COLD LAV 16PT	1
1.2	1-110	WIDESPREAD VALVE HOT LAV 16PT	1
2	10719/00	POP-UP ROD, 10-24, 14" LONG	1
3	10982	HOSE, 3/8" COMP. X 1/2" NPSM - 12"L	2
4	3-046/00	POP-UP DRAIN ASSEMBLY (2-101, 2-102)	1
5	3-330/00	SPOUT, BASIC II SERIES	1
5.1	2-109/00	SPOUT, BRAZED BUNG NIPPLE	1
5.2	10745	THREAD ALL, 3/8"-18 NPSL	1
5.3	P05061	AERATOR CACHE TINY JUNIOR 1.5GPM 43.3232.450 GREEN	1
5.4	1-112	TEE VALVE, 3/8" NPSM X 3/8" COMPRESSION	1
5.5	92174	WASHER MOUNT WIDESPREAD (3/8")	1
5.6	10746	NUT, 3/8"-18 NPSL	1
5.7	10550/00	ESCUTCHEON BASE, CONTEMP. BASIC II	1
5.8	90031	O-RING, 1-3/4TD X 1-7/8"OD X 1/16"THK, AS-568-031	1
6	3-386/00	SUB ASSY. SMOOTH HANDLE, BASIC II	2
6.1	10433/00	BASE HANDLE, CONTEMP. BASIC II	1
6.2	11164/00	ESCUTCHEON BASE, CONTEMP. BASIC II	1
6.3	92008	SET SCREW, CUP POINT 8-32	1
6.4	90031	O-RING, 1-3/4TD X 1-7/8"OD X 1/16"THK, AS-568-031	1
7	92184	HEX L-KEY 3/32" HEX x 2 1/8"L	1
8	P04019/00	POP-UP, BASIC, W/ 10-24 THREAD	1

ZONE	REV.	DESCRIPTION	DATE	APPROVED
REVISIONS				
1261 LOGAN AVENUE COSTA MESA, CALIFORNIA 92626 PHONE: 714.361.4800 FAX: 714.617.3120				
Defining Luxury Since 1959				

-		INTERPRET GEOMETRIC DIMENSIONING & TOLERANCING IN ACCORDANCE WITH ASME Y14.5-2009 & ASME Y14.41-2003 STANDARDS, UNLESS OTHERWISE SPECIFIED. DIMENSIONS ARE IN INCHES. TOLERANCES ARE:			WIDESPREAD FAUCET, SMOOTH HANDLES, BASIC II		
-		-					
NEXT ASSY	USED ON	FRACTIONS ±1/64"	DECIMALS X.X: ±.1 X.XX: ±.01 X.XXX: ±.005	ANGULAR ±5°	SIZE A	ASM/PRT NO. 230-02/00	REV -
MATERIAL	APPLICATION	NAME	DATE	DRAWN	LLO	3/12/2015	
FINISH		CHECKED	GRE	SCALE: 1:5		WEIGHT: lbs.	SHEET 1 OF 2

DO NOT SCALE DRAWING

5

4

3

2

1