

THREE HANDLE TUB AND SHOWER SET

D2130



TECHNICAL DETAILS

ADA Compliance: Yes	Water Pressure Recommended: 60 PSI
Deck Thickness Maximum: 2"	
Deck Thickness Minimum: 1/8"	
Drain Assembly Material: Brass	
Drain Style: Lift pop-up	
Fitting Hole Diameter: 1 1/8"	
Number of Holes: Three Hole	
Number of Handles: Two	
Handle Spread Maximum: 12"	
Handle Spread Minimum: 8"	
Handle Turn Angle: Quarter Turn	
Spout Reach: 7 1/2"	
Spout Height: 3"	
Inlet Connection Type: Male 1/2" NPSM	
Installation Type: Deck Mounted	
Primary Material: Brass	
Valve Material: Ceramic	
Shower Flow Restriction: 1.8 GPM	
Spout Flow Restriction: Full Flow	
Water Pressure Maximum: 85 PSI	
Water Pressure Minimum: 20 PSI	

PRODUCT FEATURES

- Style: Contemporary
- Collection: Basic
- Temperature Controlled By Handles
- Lever Handles

CODES & STANDARDS



ASME A112.181/ CSA B1251, ASME 112.18.2/ CSA B125.2, ANSI NSF, CEC, Watersense 61 Sect. 9, State of MA.

WARRANTY

Mechanical Warranty: 10 Years From Date of Purchase.
Finish Warranty: See Catalog For Further Information.

