

CODE NUMBER

12001425

DESCRIPTION

SU-1209 Urinal and SLOAN 186 SFSM Flushometer.

COMPONENTS

Flushometer: Code 3782688Urinal: Code 1101209

DETAILS

• Flush Volume: 0.125 gpf (0.5 Lpf)

Nominal Dimensions: 14 ½" × 20 ¾" × 25 ¼" (368 × 527 × 641mm)

FLUSHOMETER FEATURES

- PERMEX® high-efficiency synthetic rubber diaphragm with dual linear filtered bypass
- Four (4) size C alkaline batteries included
- "Low Battery" Flashing LED
- "User in View" Flashing LED
- No External Volume Adjustment to Ensure Water Conservation
- True Mechanical Override Flush Button
- 72-Hour Sentinel Flush
- Sweat Solder Adapter w/Cover Tube and Cast Wall Flange with Set Screw
- Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine resistance
- 3/4" IPS screwdriver Bak-Chek® angle stop with vandal resistant stop cap

FIXTURE FEATURES

- White Vitreous China
- Large footprint to cover old caulk lines
- Washdown flushing action
- Integral flushing rim
- ¾" I.P.S. top spud inlet
- 2" NPT outlet flange
- Vandal resistant strainer assembly included
- All mounting hardware included
- 100% factory flush tested



COMPLIANCES & CERTIFICATIONS









(WaterSense Listed, BAA Compliant, cUPC Green Certified, Satisfies LEED Credits)

DOWNLOADS


- SU 1200/1210 Series Installation Instructions
- EBV-500/550-A Installation Instructions
- Sloan Exposed Installation Instructions
- Sloan Flushometer Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.



ROUGH-IN



Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com