

CODE NUMBER

3365247BT

DESCRIPTION

Plug Adapter Power Supply, Below Deck Thermostatic Mixing Valve, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Hardwired-Powered Deck-Mounted Low Integrated Base Body Faucet.

DETAILS

• Flow Rate: 0.5 gpm (2 Lpm) (0.5GPM) • Spray Type: Multi-Laminar (MLM)

 Sensor Type: Infrared (IR) Mounting Type: 4" Centerset () • Power Supply: Plug Adapter (PLG)

• Temperature Mixer: Below Deck Thermostatic Mixing Valve (BDT)

• Finish: Polished Chrome (CP) • Factory Default Timeout: 30s • Factory Default GPC: 0.25

FEATURES

Commercial Grade Faucet, ADA Compliant, Cast Brass Spout, Quick Connect Fittings, Integrated Water Shut-off, Wireless Settings Adjustment, On-demand or Metered activation, Hygienic Line Flush, Water Usage and Battery Strength Reporting, Self-adapting Sensor

ELECTRICAL SPECIFICATIONS

• Battery Life: 3 years 8,000 cycles/month o Optional power harvesting significantly extends service life

 Sensor Range: 4"-5" (102-127mm) • Timeout Adjustment Settings: 30s

POWER SUPPLY OPTIONS

• 6VDC Ganged Adapter Kit (up to 6 units)(sold separately)*

• 6VDC Plug Adapter (included with PLG models)

• 24VAC Box Transformer (included with BOX models)

* when converting units to hardwired with battery back-up

VIDEOS

Sloan Connect App®

Sloan Optima Below Deck Faucet

PVD Special Finishes

DOWNLOADS

• Optima Smart Faucet Below Deck Installation Instructions


• Trim Plate Guide

• Faucet Spray Heads Repair and Maintenance Guide

• ETF-600/EBF-650 Below Deck Repair and Maintenance Guide

• Additional Downloads









(ADA Compliant, ASME A112.18.1 Compliant, ASSE 1070, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, cUPC Certified, UL Certified, UPC Certified, UPC Low Lead Compliant, cUPC Low Lead Compliant, EPD, Green Globes Materials & Resources Credit, Green Globes Water Credit, HPD, LEED Materials & Resources EPD Credit, LEED Materials & Resources HPD Credit, NYC604.4, Proposition 65, Satisfies LEED Credits, TAS, WELL Building Standard)

RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

NOTES

All information contained within this document subject to change without notice.



OPTIMA® SENSOR FAUCET ETF-600-PLG-BDT-CP-0.5GPM-MLM-IR-FCT

Looking for other variations of the ETF-600 product? View the general spec sheet with all options.


Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

WARRANTY

3 Year



ROUGH-IN



Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com