

CODE NUMBER

70001015

DESCRIPTION

SU-7009 Urinal and REGAL 186 Flushometer.

COMPONENTS

• Flushometer: Code 3982604 • Urinal: Code 1107009

DETAILS

• Flush Volume: 0.125 gpf (0.5 Lpf)

• Nominal Dimensions: $14 \frac{3}{4}$ " × $14 \frac{3}{16}$ " × $23 \frac{1}{2}$ " ($375 \times 360 \times 10^{-2}$ 597mm)

FLUSHOMETER FEATURES

- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- Control Stop Plug
- Sweat Solder Adapter with Cover Tube
- Cast Wall Flange with Set Screw
- Vacuum Breaker Flush Connection
- Spud Coupling Wall and Spud Flange for 3/4" Top Spud
- Non-Hold-Open Handle and No External Volume Adjustment to **Ensure Water Conservation**
- 3/4" I.P.S. Wheel Handle Bak-Chek® Angle Stop

FIXTURE FEATURES

- White Vitreous China
- Washdown flushing action
- Integral flushing rim
- ¾" I.P.S. top spud inlet
- 2" NPT outlet flange
- · Vandal resistant strainer assembly included
- All mounting hardware included
- 100% factory flush tested



COMPLIANCES & CERTIFICATIONS



















(ADA Compliant, BAA Compliant, BREEAM Water Credit, BREEAM Materials Credit, CalGreen Compliant, CEC Compliant, CSA Certified, cUPC Certified, cUPC Certified (Requires use of listed vacuum breaker that complies with ASSE 1001), cUPC Green Certified, cUPC Green Certified (Requires use of listed vacuum breaker that complies with ASSE 1001), EPD, Green Globes Water Credit, Green Globes Materials & Resources Credit, HPD, LEED V4 Water Efficiency Credit, LEED Materials & Resources EPD Credit, LEED Materials & Resources HPD Credit, Satisfies LEED Credits, UPC Certified, WaterSense Listed, WELL Building Standard)

DOWNLOADS

- Regal XL Exposed Installation Instructions
- Small Spud Urinal Installation Instructions
- Regal Flushometers Repair and Maintenance Guide
- SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.