Royal II® Model Flushometer

120

Description

Exposed Water Closet Flushometer for floor mounted back spud bowls.

Flush Cycle

□ Model 120-1.6 Low Consumption (1.6 gpf/6.0 Lpf) □ Model 120 Water Saver (3.5 gpf/13.2 Lpf)

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Closet Flushometer with the following features:

- PERMEX[™] Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- Aesthetically contoured Cover, Handle Socket and Flanges
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Free Spinning Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Elbow Flush Connection, Spud Coupling and Flange for 11/2" Back Spud
- Sweat Solder Adapter w/Cover Tube and Cast Wall Flange w/Set Screw
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flush Accuracy Controlled by CID[™] Technology
- Diaphragm, Handle Packing, Stop Seat and Vacuum Breaker molded from PERMEX[™] Rubber Compound for Chloramine Resistance
- 100% of the energy used in manufacturing is offset with Renewable Energy Sources – Wind Energy

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.2, and Military Specification V-29193.

Special Finishes

D PB	Polished Brass (PVD Finish)
GP	Gold Plate (PVD Finish)
□ BN	Brushed Nickel (PVD Finish)

Satin Chrome

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.



Architect



Listed by I.A.P.M.O.

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.



 SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131

 Ph: 1-800-9-VALVE-9 or 1-847-671-4300
 • Fax: 1-800-447-8329 or 1-847-671-4380

 Made in the U.S.A.
 www.sloanvalve.com



