

OPTIONS**Flush Volume**

- 3.5 gpf (13.2 Lpf) (3.5)
- 1.6 gpf (6.0 Lpf) (1.6)
- 1.28 gpf (4.8 Lpf) (1.28)

Wall Plate Finish

- Stainless Steel (BSS)

Water Efficiency

- Water Saver
- High Efficiency
- Low Consumption

L Dimension

- 2 ¾" (70mm) (2-3/4-LDIM)
- 3 ¾" (95mm) (3-3/4-LDIM)
- 10 ¾" (273mm) (10-3/4-LDIM)

Wall Box

- Standard (WB)

Push Button

- 3" Metal Oscillating (L3)
- Less (L/C9A)

Adapter

- Sweat Solder Adapter Kit (YB)

Compliances & Certifications

- BAA Compliant
- UPC Certified
- cUPC Certified
- Satisfies LEED Credits
- WaterSense Listed
- cUPC Green Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard SLOAN 150 shown

DESCRIPTION

Sloan® Concealed Manual Flushometer

FEATURES

- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Concealed Flushometers Repair and Maintenance Guide](#)
- [Sloan/Regal ESS Repair and Maintenance Guide](#)
- [Additional Downloads](#)