



Water Closet



Combination Fixture





Hydraulic Sloan® **Prison Model Flushometer**



Description

Concealed Hydraulically Activated Water Closet Flushometer, for Stainless Steel back spud water closets and Combination Fixtures. For use with: Acorn® • Bradley® • Metcraft[®] • Willoughby[®] and similar fixtures.

Flush Cvcle

Model 9603 Water Saver (3.5 gpf/13.2 Lpf)

Model 9603-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Closet Flushometer for either left or right hand supply with the following features:

- High Chloramine Resistant PERMEX[™] Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action™
- ADA Compliant Non-Hold-Open feature type Actuator (specify Actuator type listed below)
- 1" I.P.S. Wheel Handle Bak-Chek® Angle Stop
- · Adjustable Tailpiece
- High Back Pressure Vacuum Breaker
- Elbow Flush Connection and Coupling for 1-1/2" NPT Back Inlet (for connection in the pipe chase — flush connection through the wall not provided by Sloan)
- Exposed parts Chrome Plated • High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Push Button, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Low Consumption Flush Accuracy
- Handle Packing, Stop Seat and Vacuum Breaker molded from PERMEX[™] Rubber Compound for Chloramine Resistance
- 100% of the energy used in manufacturing is offset with Renewable Energy Sources - Wind Energy

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

Actuator Types: (please check one)

□ MBFW Metal Button Fixture Wall Actuator (HY-100-A) (rear access) **MBPM** Metal Button Panel Mount (HY-108-A) for use only with Wall Box or when Access Panel is provided in combination fixture

Variations

□ AFD Shorter Vacuum Breaker - for use with Anti-Flood Device

(Anti-Flood Device NOT provided by Sloan) Dual Filtered Fixed Bypass Diaphragm

Sweat Solder Adapter



This space for Architect/Engineer approval	
Job Name	Date
Model Specified	Quantity
Variations Specified	
Customer/Wholesaler	
Contractor	
Architect	

The information contained in this document is subject to change without notice



Sloan Prison 9603 S.S. — Rev. Oc (11/10) Copyright © 2010 SLOAN VALVE COMPANY