

OPTIONS**Flush Volume**

- 1.6 gpf (6.0 Lpf) (1.6)
- 1.28 gpf (4.8 Lpf) (1.28)

Finish

- Polished Chrome (CP)
- Polished Brass (PB)
- Brushed Nickel (BN)
- Brushed Stainless (SF)

Water Efficiency

- Low Consumption
- High Efficiency

Handle

- Front of Valve (H)
- Sanigard® (SG)
- Left of Valve (G)
- Nickel-Silver (YA)
- Right of Valve (I)

Push Button

- 3" Metal Oscillating (L3)
- Metal Index (L)
- Front of Valve (HL3)

Control Stop

- 1" Straight (E)
- Wheel Handle (K)
- Ground Joint (GJ)
- Less (L/STOP)

Tailpiece

- H551A 3 1/16" (H551A-3-1/16)
- H551A 4 1/16" (H551A-4-1/16)
- H551A 5 1/16" (H551A-5-1/16)

Inlet

- Back of Valve (B)
- Left of Valve (C)

Vacuum Breaker


- Less (XYV)

Offset

- 1 ½" (38mm) (1-1/2-OFST)
- 1" (25mm) (1-OFST)

Outlet Tube

- Trap Primer (TP)
- F189 (F189)

**DESCRIPTION**

Royal® Exposed Manual Flushometer

FEATURES

- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Royal Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Royal Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

F188 (F188)

Bumper

- Angle Stop (YO)
- Angle Stop Extended (YG)

Pipe Support

- Solid Ring (YK)

Special Features

- Less Logo (LL)
- Whitworth Thread (WWT)

Compliances & Certifications

- BAA Compliant
- cUPC Certified
- ADA Compliant
- Satisfies LEED Credits
- WaterSense Listed
- cUPC Green Certified
- Red List Free
- Declare
- EPD
- HPD

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.