

OPTIONS**Flush Volume**

- 3.5 gpf (13.2 Lpf) (3.5)
- 1.6 gpf (6.0 Lpf) (1.6)
- 6.5 gpf (24.6 Lpf) (6.5)

Wall Plate Finish

Stainless Steel (BSS)

Water Efficiency

Water Saver
Low Consumption

L Dimension

- 6 ¾" (171mm) (6-3/4-LDIM)
- 8 ¾" (222mm) (8-3/4-LDIM)
- 10 ¾" (273mm) (10-3/4-LDIM)
- 3 ¾" (95mm) (3-3/4-LDIM)
- 2 ¾" (70mm) (2-3/4-LDIM)
- 4 ¾" (121mm) (4-3/4-LDIM)
- 7 ¾" (197mm) (7-3/4-LDIM)
- 5 ¾" (146mm) (5-3/4-LDIM)
- 12 ¾" (324mm) (12-3/4-LDIM)
- 11 ¾" (298mm) (11-3/4-LDIM)

Wall Box

Standard (WB)

Handle

Metal Oscillating (J)
Front of Valve (H)

Push Button

3" Metal Oscillating (L3)
C2A (C2A)
Front of Valve (HL3)

Control Stop

1" Straight (E)
Ground Joint (GJ)
Less (L/STOP)

Vacuum Breaker

Less (XYV)

Compliances & Certifications

BAA Compliant
UPC Certified
cUPC Certified
UL Certified



Image for a standard ROYAL 150 shown

DESCRIPTION

Royal® Concealed Manual Flushometer

FEATURES

- Flush volumes start as low as 1.28 gpf/4.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Concealed Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.