

OPTIONS**Flush Volume**

3.5 gpf (13.2 Lpf) (3.5)

1.6 gpf (6.0 Lpf) (1.6)

Wall Plate Finish

Stainless Steel (BSS)

Water Efficiency

Water Saver

Low Consumption

L Dimension

11 ¾" (298mm) (11-3/4-LDIM)

7 ¾" (197mm) (7-3/4-LDIM)

10 ¾" (273mm) (10-3/4-LDIM)

8 ¾" (222mm) (8-3/4-LDIM)

12 ¾" (324mm) (12-3/4-LDIM)

13 ¾" (349mm) (13-3/4-LDIM)

14 ¾" (375mm) (14-3/4-LDIM)

15 ¾" (400mm) (15-3/4-LDIM)

17 ¾" (451mm) (17-3/4-LDIM)

20 ¾" (527mm) (20-3/4-LDIM)

Wall Box

Standard (WB)

Push Button

Less (L/C9A)

Control Stop

1" Straight (E)

Adjustable Ground Joint (ADJ/GJ)

Compliances & Certifications

BAA Compliant

UPC Certified

cUPC Certified

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ROYAL 681 shown

DESCRIPTION

Royal® Concealed Manual Flushometer

FEATURES

- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan Stainless Steel Installation Instructions](#)
- [Additional Downloads](#)