




LATINA

K-146


PULL DOWN WITH DUAL FUNCTION
KITCHEN FAUCET



RECOMMENDED ACCESSORIES



HANDLE TYPE



NUMBER OF HANDLE



CARTRIDGE MODEL

Kerox®

SIZE: 35mm
STYLE: LEVER

SPRAY SETTINGS



SPRAY WATER FLOW / AERATED STREAM

FAUCET FINISH



PRODUCT DIMENSIONS

Faucet Height (in)	13 1/8"
Spout Height (in)	11 1/2"
Spout Reach (in)	8 5/16"

CONFIGURATION



1-HOLE

3-HOLES

SPOUT SWIVEL (DEGREES)



MATERIAL



STAINLESS STEEL

CUT OUT HOLE



DECK PLATE

NO INCLUDED.
REQUIRED FOR 3
HOLES INSTALLATION

WATER FLOW

1.8

WATER FLOW RATE
(GPM)

WATERLINES MODEL



CONNECTIONS 3/8"

WARRANTY

This product is covered by a limited lifetime warranty.
Consult our website for complete details.

PRODUCT CARE

- Wipe faucet with damp cloth and mild household cleanser.
- Dry with soft cloth to maintain original appearance.
- Remove hard water stains with 50/50 solution vinegar and water.
- If mineral deposits are too hard to remove, specially in the aerator, unscrew aerator by hand or with tool provided with faucet, soak aerator in 50/50 vinegar and water solution for several hours, rub your fingers and use a tooth brush to remove mineral deposits, place aerator back into original position.



STANDARDS COMPLIANCE



AERATOR
Neoperl®

Stylish International Inc.

www.stylishkb.com

[stylish.international.inc](https://www.instagram.com/stylish.international.inc)

care@stylishkb.com

+1-855-789-5352




LATINA

K-146

ROBINET DE CUISINE
DOUBLE FONCTION ESCAMOTABLE



DIMENSIONS



ACCESSOIRES RECOMMANDÉS



A-802
PLAQUE DE ROBINET

S-01
DISTRIBUTEUR DE SAVON

TYPE DE POIGNÉE



LEVIER

NOMBRE DE POIGNÉE

1

MODÈLE DE CARTOUCHE

Kerox®

TAILLE: 35mm
STYLE: LEVIER

RÉGLAGE DE PULVÉRISATION



DÉBIT D'EAU DE PULVÉRISATION / FLUX AÉRÉ

FINITION DU ROBINET



BROSSÉ (S)



NOIR MAT (N)



NOIR MAT/
DORÉ (NG)



NOIR MAT/
BROSSÉ (NS)

DIMENSIONS DU PRODUIT

Hauteur du robinet (po) 13 1/8"

Hauteur du bec (po) 11 1/2"

Portée du bec (po) 8 5/16"

CONFIGURATION



1-TROU

3-TROUS

BEC PIVOTANT (DEGRÉS)



360°

MATÉRIEL



ACIER INOXYDABLE

TAILLE DE LA COUPE



PLAQUE DE PLATEAU

NON INCLUS.
REQUIS POUR UNE
INSTALLATION A
3 TROUS

DÉBIT D'EAU

1.8
DÉBIT D'EAU
(GPM)

MODÈLE DE FLOTTAISON



CONNEXIONS 3/8"

GARANTIE

Ce produit est couvert par une garantie à vie limitée.
Consultez notre site internet pour obtenir tous les détails.

ENTRETIEN

- Essuyez le robinet avec un chiffon humide et un nettoyant ménager doux.
- Séchez avec un chiffon doux pour conserver l'apparence d'origine.
- Enlevez les taches d'eau calcaire avec un mélange de 50 % d'eau et 50 % de vinaigre.
- Si les dépôts de minéraux sont trop difficiles à enlever, spécialement dans l'aérateur, dévissez-le à la main ou à l'aide d'un outil fourni avec le robinet, trempez-le dans un mélange de 50 % d'eau et 50 % de vinaigre pendant plusieurs heures, utilisez une brosse à dents pour éliminer les dépôts de minéraux, et remplacez-le dans sa position originale.



NORMES CONFORMES



AÉRATEUR
Neoperl®

Stylish International Inc.

www.stylishkb.com

[stylish.international.inc](https://www.instagram.com/stylish.international.inc)

care@stylishkb.com

+1-855-789-5352