

PRODUCT REFERENCE INFORMATION Model: WCT6920WS, Cat. No. F4482 Weight 330 lbs 38" Height Width 37-1/4" Depth 25-1/8' Firebox W x H x D 22" x 11-3/4" x 12" measured in front




Rough Framing Face (dimension includes finish material inside framing, if any)

Framing Dimensions


- * For flush framing installations
- Combustible materials can NOT be used in the space directly above the fireplace. Do not fill the space above the fireplace with any material (Except the wood framing)






Back Wall of Chase / Enclosure Including Finishing Materials, if any

Outside Chase






NOTES

Diagrams, illustrations and photographs are not to scale - consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.


All framing dimensions include sheathing.

* The fireplace must not be in contact with any insulation or loose filling material. Cover the insulation with drywall panels around the fireplace.



6 (153) -7-7/8 (200) 9-3/4 (248)

56 (1422) 12-1/4 (311) 22-5/8 (575) **To standoffs



INSTALLATION ACCESSORIES


- **6" diameter chimney United States** Model IHP Snap-Pak, including:
- Chimney lengths
- Elbows (where necessary)
- Associated components as per these
- installation instructions
 6" diameter chimney Canada *
 Security Chimney: Secure Temp ASHT+ or
- S2100+, DuraVent: DuraTech Canada or Duratech Premium, including:
 - Chimney lengths
 - Elbows (where necessary)
- Associated components as per the installation instructions & instructions provided by the venting manufacturer **Decorative Door** - Required
- (Order Separately) Front Facade kit - Required
- (Order Separately)
- UZY6-B Blower Kit (included)
- VRUW Blower Speed Control (included)
 Outside Air Kit (Included)
- Heatflo Convection Kit (optional)
- Forced Air Kit (optional)
 Finishing Guide Plate (included on Fireplace)

*Available from Security Chimneys™

Inches (millimeters)

Page 1 of 2

EPA Wood Burning Fireplaces Specifications



CLEARANCE TO COMBUSTIBLES

The following clearances meet the minimum requirements for a safe installation:

Side wall: 24" (610 mm) measured from the firebox opening.

Ceiling: 6' 8" (2032 mm) measured from the base of the fireplace.

Fireplace enclosure:

Bottom: 0"

Side: 0" to spacer Back: 0" to spacer


Top: Do not fill the space above the fireplace with any material (Except the wood framing)

Chimney: 2" (50 mm)

Mantel: 39-1/2 (1004mm) minimum above base of unit.

16" (407mm) maximum depth.

NOTE: Only non-combustible mantels may be used.



Printed in U.S.A. © 2019 Innovative Hearth Products **P/N 900995-01, REV. B, 03/2021**

