TOTO_®

MW6263056CEFG(A)

Aimes® WASHLET®+ S550e One-Piece Toilet - 1.28 GPF

FEATURES

- Concealed supply connection for seamless installation
- TORNADO FLUSH® system, high-efficiency (1.28 GPF/4.8 LPF)
- CEFIONTECT® ceramic glaze prevents debris and mold from sticking to ceramic surfaces
- Completely skirted design for a sleek and understated look that's easier to clean
- Universal Height
- 12" Rough-in
- Chrome plated trip lever
- Elongated front bowl and WASHLET+ S550e and tank set
- EWATER+® auto-cleans wand and bowl
- On-demand remote function cleans wand with EWATER+
- PREMIST of bowl before each use
- Remote control operated
- Auto Flush available as upgrade
- Auto Open / Close lid
- Night light

MODELS

MW6263056CEFGA (#01)

With CEFIONTECT ceramic glaze, WASHLET+ S550e with contemporary design and Auto Flush

- CST626CEFGAT40
 Elongated toilet with CEFIONTECT
- SW3056AT40 WASHLET+ S550e - Auto Flush compatible
- **THU767** Auto Flush Kit
- MW6263056CEFG (#01)

Same as MW6263056CEFGA without Auto Flush

- CST626CEFGT40
 Elongated toilet with CEFIONTECT
- SW3056T40 WASHLET+ S550e - Non Auto Flush compatible

Optional Components

- TSU03W.10R 10" Unifit Rough-In
- TSU03W.14R
 14" Unifit Rough-In
- THU311N#PN Trip Lever - Polished Nickel
- THU311N#BN
 Trip Lever Brushed Nickel

COLORS/FINISHES

#01 Cotton













PRODUCT SPECIFICATION

The one-piece high-efficiency TORNADO FLUSH system toilet shall be 1.28 GPF/4.8 LPF. Toilet shall be 12" Unifit rough-in. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl with Polished Chrome trip lever. Toilet shall be TOTO Model MW6263056CEFG__#01

See SW3046(A)T40 Specification Sheet for details on included WASHLET.

CODES/STANDARDS

- Meets or exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA Watersense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements







Aimes® WASHLET®+ S550e One-Piece Toilet - 1.28 GPF

SPECIFICATIONS


	4.00 CDE (4.0 LDE)
Water Use	1.28 GPF (4.8 LPF)
Flush System	TORNADO FLUSH®
Min. Water Pressure	8 psi (Flowing)
Water Surface	7-3/4" x 9-3/8"
Trap Diameter	2-1/8"
Rough-in	12" (10" & 14" Optional)
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	119 lbs
Shipping Dimensions	32"L x 20"W x 17-3/4" H ¹ x 28-3/4" H ²

See SW3046(A)T40 Specification Sheet for details on included WASHLET.

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS

