

TLG08201U

GC Widespread Faucet

FEATURES

- WaterSense® certified low-flow 1.2 gpm faucet
- Brass construction
- Accommodates 8"-11" spread
- Metal pop-up drain assembly included

COLORS/FINISHES

- #CP Polished Chrome
- #PN Polished Nickel
- #BN Brushed Nickel

Made to Order

- #PFG Polished French Gold
- #PBR Polished Bronze
- #PBL Polished Black*
- #PRG Polished Rose Gold*
- #MBL Matte Black*
- #BRG Brushed Rose Gold* *Available 2021

PRODUCT SPECIFICATION

Product shall have a maximum flow rate of 1.2 gpm (4.5 lpm). Product shall have a brass construction. Product shall have lever handles. Product shall have a ceramic disk valve cartridges. Product shall include metal pop-up drain assembly. Product shall be TOTO Model TLG08201U#____.

CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1, NSF 61-9, NSF 372
- Certifications: IAPMO(cUPC), EPA WaterSense, State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, CEC, DoE, NPC Canada, and others
- California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- Complies with federal and state requirements as lead-free (weighted average of 0.25% lead or less)
- Complies with CA Prop 65 warning requirements







GC Widespread Faucet

SPECIFICATIONS

| Material | Brass |
|-------------------|--|
| Maximum Flow Rate | 1.2 gpm (4.5 lpm) |
| Warranty | Lifetime Limited Warranty (Residential Use) One Year (Commercial Use) |



DIMENSIONS



The dimension in () is mm.

TOTO_®