TOTO

TS200A55 & TS200A65

Transitional Series A Multi-Spray Showerhead

FEATURES

- Maximum flow rate of 2.5 gpm (9.5 lpm)
- Multifunction showerhead with 5 spray modes
 - Spray
 - Spray & Massage Combo
 - Massage
 - Mist
 - Pause
- Rubber nozzles to prevent limescale build up
- G 1/2" connection

MODELS

- TS200A55
 4-1/2" showerhead
 4" diameter spray face
- TS200A655-1/2" showerhead5" diameter spray face

COLORS/FINISHES

- #CP Polished Chrome
- #BN Brushed Nickel
- #PN Polished Nickel

CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Complies with CA Prop 65 warning requirements



PRODUCT SPECIFICATION

The multi-spray showerhead shall have a maximum flow rate of 2.5 gpm (9.5 lpm). TS200A55 shall have a 4-1/2" showerhead and a 4" diameter spray face. TS200A65 shall have a 5-1/2" showerhead and a 5" diameter spray face. Product shall have 5 multifunction spray modes. Spray modes shall be spray, spray and massage combo, massage, mist and pause. Product shall have rubber nozzles to prevent limescale build up. Product shall be TOTO Model TS200A____ #____.



TS200A55: Transitional Series A Multi-Spray Showerhead 4-1/2"



TS200A65: Transitional Series A Multi-Spray Showerhead 5-1/2"

Please note the following component is sold separately:



TS200N6: Shower Arm 6"

Transitional Series A Multi-Spray Showerhead

SPECIFICATIONS

Warranty
 Lifetime Limited Warranty

(Residential Use)


One Year (Commercial Use)

 Material Brass / Plastics
 Shipping Weight TS200A55: 0.9 lbs. TS200A65: 1.0 lbs.

Shipping Dimensions TS200A55 & TS200A65:


3-1/2"L x 5-3/4"W x 6-3/4"H


Maximum Flow Rate 2.5 gpm (9.5 lpm)



INSTALLATION NOTES

OPTIONAL SHOWERHEAD COMPONENT: TS200N6: Shower Arm 6" sold separately.







These dimensions and specifications are subject to change without notice