


## INDUSTRIAL PLP PULLDOWN FAUCET / ANGLED SPOUT / 3PC. SUITE 9410-3

- Max Counter Thickness 2-3/8"
- Minimum Install Hole Size 1-1/2"

- A. Spray Connection with 3/8" Compression Fitting
- B. Supply Hoses - 20" Long with 3/8" Compression Fittings



**DIMENSIONS MAY VARY AND ARE SUBJECT TO CHANGE. NO RESPONSIBILITY IS ASSUMED FOR USE OF SUPERCEDED OR VOIDED DATA**

## INDUSTRIAL PLP PULLDOWN FAUCET / ANGLED SPOUT / 3PC. SUITE **9410-3**



Finish Shown - Polished Nickel

### **FEATURES**

- 3pc. Suite includes faucet, soap/lotion dispenser and air switch.
- Thinner, sleek faucet body design.
- Decorative knurling gives industrial look.
- 7 degree angled spout flows outward towards middle of sink.
- "Positive Lock Pulldown" design locks sprayer in place when not in use.
- Spout has 9" reach and can swivel 360 degrees.
- Toggle handle spray head pulls out 18" from spout.
- Counterbalanced weight on spray hose allows smooth pull out and prevents snap back.
- Sprayer instantly diverts water from aerated stream to wide spray when handle is held.
- 1.75 gpm maximum flow rate with aerated tip.
- Innovative handle tension system prevents sagging.
- Single handle can mount in front, right or left hand positions.
- When mounted on side, handle can adjust 22.5 degrees for backsplash clearance.
- Hot/cold ceramic disk valve cartridge.
- Resistant to reverse osmosis water.
- Made from solid brass or 316 stainless steel.
- Lifetime functional warranty.

### **CODES/STANDARDS APPLICABLE**

Specified model meets or exceeds the following:

- **ASME A112.18.1**
- **CSA B125.1**
- **NSF 61, 372**
- **CALGreen**



**AVAILABLE IN 32 FINISHES + SOLID 316 MARINE GRADE STAINLESS STEEL**